

QwikInjector® with QwikShot® Acid Flush™

QwikInjector® Additive Injection Tool now comes with a **FREE bottle** of QwikShot® Acid Flush™

QwikInjector® is used to drive any liquid (such as QwikShot®) into the low side of a charged system. It is compatible with all refrigerants and oils, including R-410A. This rugged aluminum tool is used with any ordinary gauge set to inject liquid additives into the system.

- Available as a ½ oz. vessel
- Tested & Approved for R-410A
- Compatible with oils, dyes and QwikShot® Acid Flush™

Directions for use:

1. Always connect the QwikInjector® to the low side of an operating system before connecting to the high side.
2. Never leave the QwikInjector® connected to the hoses. After use, always disconnect and disassemble.
3. Before unscrewing the cover, always check for any pressure build up by depressing the valve core depressor.
4. Always store the QwikInjector® with the cap screwed on loosely to prevent thread binding and pressure build-up.

For more details or information about QwikInjector® or QwikShot® Acid Flush™ visit www.qwik.com

QwikInjector® Additive Injection Tool now with Free QwikShot® Acid Flush™
Part # QT2510 (Injector w/Acid Flush) or Part # QT2500 (Acid Flush alone)

QwikProducts™ and Acid Flush™ are trademarks of Mainstream Engineering Corporation. QwikInjector® and QwikShot® are registered trademarks of Mainstream Engineering Corporation, Rockledge, Florida 32955, (321) 631-3550
U.S. Patents #5,770,048 & #5,996,651 All QwikProducts™ are made in the USA

