

QWIKSOAKER

Foaming Gun

QT2710

QwikSoaker delivers rich foam for faster, more effective cleaning.

The **QwikSoaker** Foaming Gun connects to a standard garden hose to create rich, clinging foam for faster and more effective HVAC coil cleaning. Its adjustable dilution dial allows precise cleaner-to-water mixing, while the ergonomic trigger and foaming nozzle provide consistent, easy application on coils, fan blades, and other HVAC components.

Designed for both professional technicians and maintenance personnel, the **QwikSoaker** helps improve cleaner coverage and contact time on dirty surfaces. Durable and easy to use, it's an ideal tool for routine HVAC cleaning and maintenance.

QT2782

QWIKBRIGHT®

Coil Cleaner & Protectant

QwikBright is a neutral pH microchannel coil cleaner and protectant that is specially formulated to quickly penetrate and dissolve grease, grime, lint, dirt, dust, and bugs while adding a metal protecting film. That's right, **QwikBright** contains a molecular metal protectant to further prevent corrosion without degrading thermal performance.

DIRECTIONS FOR USE



1. Always wear goggles, gloves, protective clothing, and a full face shield.
2. Make certain the unit is off and disconnected.
3. Using **QwikSoaker (QT2710)** adjust dial to desired dilution ratio. For heavy duty applications, use the 1:5 ratio (setting E) with **QwikBright**. Spray onto the dirty coil and allow **QwikBright** to remain in contact with the dirty surfaces for 5 – 10 minutes.
4. Rinse the coil thoroughly with clean water until no cleaner is present on the coils.

For more details or information about **QwikBright** and **QwikSoaker** scan below:



qwik.com/qwikbright-coil



qwik.com/qwiksoaker

QwikProducts®, and **QwikBright®** are registered trademarks of Mainstream Engineering Corporation. Rockledge, Florida 32955, (321) 631-3550



QwikSoaker Dilution Table

A	1:80	1.5 oz/gal
B	1:40	3 oz/gal
C	1:20	6 oz/gal
D	1:15	8 oz/gal
E	1:5	21 oz/gal
Ø	Water Only	Water Only

